



## Direct-Lift X-FORCEUTV

## LB. CAPACIT





## Pedestal mounted controls

Efficient and easy to use, power units feature a heavyduty electric 115v motor with single "up" button switch and a single lowering valve release handle. The air operated lock release operates at 90 psi.

Specifications	X-FORCE UTV
Capacity	2,275 lbs.
Maximum Rise*	78 - 5/8"
Lowered Height	4 - 1/8"
Overall Width	26 - 3/8"
Overall Length	85"
Platform Width	24 - 3/4"
Platform Length	59"
Ramp Length	13"
Distance from Console to Lift (Max)	85"
Motor / Voltage	1Ø 2 HP / 115v
Time of Full Rise	40 seconds
Compressed Air Connection	85 - 110psi

<sup>\*</sup> Rise measures floor to top of runway at full stroke



**Load bearing hinged ramps** with polymer rollers allow additional access to perform wheel / brake work. The ramps fold up, lock in place and increase lifting capabilities by extending the pick-up point surface area. Hinged ramps fold 65 degrees down and away, allowing for more access to service vehicle.



**Multiple lock positions** with negative rake tooth design provides stable support at all heights.

## **Adapter contact options**

Polymer rubber adapter pads are used for vehicle contact. Lift comes standard with a set of four 1-1/2"

and set of four 3" flat polymer rubber pad adapters.



996 Industrial Drive Madison, Indiana 47250

Toll free: 866.347.5438

International sales:812.273.1622

